



尺寸	型 号	PKWO-1038	PKWO-1538	PKWO-2045	PKWO-2545	PKWO-4057
ΦD		114	140	140	140	165
L1		1000	1040	1340	1740	1900
L2		856	936	1236	1536	1796
L3		450	550	840	1240	1240
L4		608	608	1048	1430	1500
F		120	120	120	120	315
G		168	180	180	180	220
H		237	260	260	260	160
ΦZ		12	12	12	12	12
技术数据						
水温35℃换热量	Kw	4.6~8.2	10.3~17.6	18.6~27.2	29.8~45.5	42.5~70.0
水流量	m³/h	2.0~4.5	3.0~6.0	3.0~6.5	3.0~7.5	3.4~10.0
压 降	Bar	0.22	0.23	0.24	0.25	0.35
油流量	m³/h	0.5~0.7	0.7~1.4	1.4~2.2	2.1~3.8	2.9~5.5
油侧内部容积	L	4.7	10.3	11.6	15.5	23.8
油侧最大工作压力	Bar	28	28	28	28	28
水侧最大工作压力	Bar	10	10	10	10	10
接口尺寸						
① 油进口		Φ38	Φ38	Φ45	Φ45	Φ57
② 油出口		Φ38	Φ38	Φ45	Φ45	Φ57
③ 进水口		G1"	G1"	G1-1/4"	G1-1/4"	G1-1/2"
④ 出水口		G1"	G1"	G1-1/4"	G1-1/4"	G1-1/2"
⑤ 检修阀接口		1/2"-14NPT	1/2"-14NPT	1/2"-14NPT	1/2"-14NPT	1/2"-14NPT
⑥ 排污口		1/2"-14NPT	1/2"-14NPT	1/2"-14NPT	1/2"-14NPT	1/2"-14NPT
⑦ 放油口		1/2"-14NPT	1/2"-14NPT	1/2"-14NPT	1/2"-14NPT	1/2"-14NPT

